



Superior  
Manufacturing  
Group, Inc.

[www.MattingExperts.com](http://www.MattingExperts.com)

Toll Free (800) 858-3417  
Int'l. +1(301) 734-6036  
Fax. +1(267) 295-8676

**139 Boulevard™**  
Entrance Matting

Available Colors: Navy, Charcoal, Brown, Red/Black,  
Hunter Green, Burgundy



Good Better Best Superior



**B**oulevard™ has a unique high-low wave design of alternating Decalon® drying yarn and Decalon® yarn wrapped with a tough mono-filament for ultra-aggressive scraping. Its 40 ounces of tufted yarn per square yard offer the ultimate in moisture absorption and crush resistance standing up to the heaviest traffic areas. A heavyweight vinyl backing in corresponding colors ensures minimum mat movement and enhances the aesthetic appeal of the mat. Boulevard's colors correspond with the Uptown™ mat to be used together as an upscale scrape & dry entrance matting system

Test	Test Description	*Results
Abrasion Resistance ASTM D3884-01	Test specimen is subjected to the rubbing action of two abrading wheels under controlled conditions. Results measured in Weight loss (Grams)	N/A
Accelerated Wear ASTM D5252-98a	Using a Hexapod Tumble Drum tester, after a specified number of cycles, the test specimen is assessed for appearance change and color change.	Number of cycles - 4,000 Appearance rating - 2.2 Color change rating - 4.0
Accelerated Soiling ASTM D6540-00	Test specimen is subjected to an accelerated soiling process. for a predetermined length of time. The sample is vacuumed, rated, submitted to an extraction device, then rated again.	(Based on visual inspection) 4.5 - Vacuum Rating 5 - Rating After Extraction
Water Retention	Test specimen is submerged in water for 5 minutes, removed, drained for 15 seconds and weighed. Results measured in weight gain. (Gallons per sq. yd.)	.882
Flammability ASTM D2859 (CPSC FF 1-70)	Intended to measure the matting's response to an ignition source in a controlled environment. The uncharred area of the test specimen must be greater than 1 inch to pass.	3.6 Inches <i>Note - Passes Federal Flammability Std. DOC FF 1-70</i>

\*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.

AATCC Rating Key (For Accelerated Soiling Test)	
5	No change
4	Slight change
3	Noticeable change
2	Considerable change
1	Severe change

Appearance Rating Key (For Accelerated Wear Test)	
5	No change
4	Slight change
3	Noticeable change
2	Considerable change
1	Severe change

Color Change Rating Key (For Accelerated Wear Test)	
5	No change
4	Slight change
3	Noticeable change
2	Considerable change
1	Severe change



Custom Lengths

- Face Weight: 40 oz. per sq. yd.
- Thickness: 3/8"
- Vinyl Backing reduces mat movement
- Stock Sizes: 2' x 3', 3' x 4', 3' x 5', 3' x 6', 3' x 10', 4' x 6', 4' x 8'
- Roll Sizes: 3' x 60', 4' x 60', 6' x 60'
- Custom Sizes available in 3', 4', and 6' widths



RESULTS from INDEPENDENT TEST LABS & PRESENTED as COMPARISONS to OTHER NoTRAX® ENTRANCE MATS