



Superior
Manufacturing
Group, Inc.

www.MattingExperts.com

Toll Free (800) 858-3417
Int'l. +1(301) 734-6036
Fax. +1(267) 295-8676

166 Guzzler™
Entrance Matting



AquaTRU™

Available Colors: Burgundy, Brown, Charcoal, Blue,
Hunter Green, Gray, Red/Black

NO TRAX®
FLOOR MATTING

Good Better Best Superior



Guzzler is part of the AquaTRU™ series of entrance mats that offer truer size options for a better value. Intended for use in medium to heavy traffic areas, the raised, crushproof waffle design of Guzzler™ aggressively scrapes and cleans, while the rubber-edged perimeter entraps dirt and moisture for superior water and soil control. Molded rubber "cleats" on the underside of the mat grip the underlying surface minimizing mat movement.

Test	Test Description	*Results
Abrasion Resistance ASTM D3884-01	Test specimen is subjected to the rubbing action of two abrading wheels under controlled conditions. Results measured in Weight loss (Grams)	0.99 Grams (3.1%)
Accelerated Wear	Test specimen is subjected to the action of rollers under a specified load. Sample is rotated 10° after each pass. Results measured in thickness loss (%)	14.48%
Accelerated Soiling ASTM D6540-00	Test specimen is subjected to an accelerated soiling process for a predetermined length of time. The sample is vacuumed, rated, submitted to an extraction device, then rated again.	(Based on visual inspection) 3.5 - Vacuum Rating 4.0 - Rating After Extraction
Water Retention	Test specimen is submerged in water for 5 minutes, removed, drained for 15 seconds and weighed. Results measured in weight gain. (Gallons per sq. yd.)	.427
Flammability ASTM D2859 (CPSC FF 1-70)	Intended to measure the matting's response to an ignition source in a controlled environment. The uncharred area of the test specimen must be greater than 1 inch to pass.	3.4 Inches Passes Federal Flammability Standard DOC FF 1-70

*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.

AATCC Rating Key (For Accelerated Soiling Test)	
5	No change
4	Slight change
3	Noticeable change
2	Considerable change
1	Severe change



- Face Weight: 26 oz. per sq. yd.
- Thickness: 1/4" pile height
- Stock Sizes: 2' x 3', 3' x 4', 3' x 5', 3' x 10',
4' x 6', 4' x 10'



RESULTS from INDEPENDENT TEST LABS & PRESENTED
as COMPARISONS to OTHER NoTRAX® ENTRANCE MATS