



Superior
Manufacturing
Group, Inc.

www.MattingExperts.com

Toll Free (800) 858-3417

Int'l. +1(301) 734-6036

Fax. +1(267) 295-8676

680 Safety Trax™
Entrance Matting



NO TRAX
FLOOR MATTING

Specialty



Available Colors: Black

Safety Trax™ are slip resistant pads that can be affixed to surfaces to increase friction and provide a safer pathway. The top surface is embedded with silicon carbide particles for aggressive traction especially in areas where there are inclines or ramped walkways. Pressure adhesive backing allows for easy "peel and stick" installation.

Test	Test Description	*Results
Coefficient of Friction ASTM C1028-96	A neolite heel assembly with a predetermined load is pulled horizontally with a dynamometer to measure the force required to cause the assembly to slip.	1.17
Abrasion Resistance ASTM D3884-01	Test specimen is subjected to the rubbing action of two abrading wheels under controlled conditions. Results measured in Weight loss (Grams)	.30 Grams

*All testing of NoTrax® floor matting has been performed by an independent testing laboratory.



- Pressure adhesive backing allows for easy "peel and stick" installation
- An optional edge sealing compound is recommended for applications exposed to water, grease or oil.
- Stock Sizes: (Rolls) 1" x 60', 2" x 60', 3" x 60', 4" x 60', 6" x 60', 12" x 60', 24" x 60'



Anti-Slip